PHOTOGRAPHIC INTERPRETATION REPORT



## WYAL DEPENDS 22PY

## INSTRUMENTATION SITE 15 SARY-SHAGAN ANTIMISSILE TEST CENTER USSR

25X1

MARCH 1967 COPY **116** 14PAGES

25X1

**Declass Review by NIMA/DOD** 

GROUP 1: EXCLUDED FROM AUTOMATIC DOWNGRADING AND DECLASSIFICATION

Approved For Release 2004/01/14 : CIA-RDP78T04759A006 00010035-9

Approved For R<del>eleas</del>e <u> 2</u> թ 4 - 14 - CIA-RDP 78 T 0 4 7 5 9 A 0 0 6 4 0 0 0 1 0 0 3 5 -

25X1

PHOTOGRAPHIC INTERPRETATION REPORT

## INSTRUMENTATION SITE 15 SARY-SHAGAN ANTIMISSILE TEST CENTER USSR

MARCH 1967

NATIONAL PHOTOGRAPHIC INTERPRETATION CENTER

	TOP SECRET	2
X1		
Λ1		
	·	
	PREFACE	
	sponse to CIA Requirement C-DI5-82,750 (revised) requesting detailed line drawings, to scale, of selected facilities at the Sary-Shagan Antimissile Test Center, USSR. The basic layout contained herein was compiled from photography obtained on Individual reports will be updated periodically to reflect changes observed on subsequent photography.  The precision target plots included in this report are mathematically rec-	
(1	tified projections of the area. Plots are compiled utilizing precision mensuration instruments, and image interpretation is performed with the aid of stereoscopic viewing equipment. Identifiable image points are measured and their coordinate values mathematically transformed by computer. This transformation corrects for camera and attitude (pitch, roll, and yaw) induced distortions, but does not correct for displacement due to ground relief and object height.  These target plots represent the most accurate data compiled to date, but the user is cautioned to exercise care in scaling distances or determining azimuths from these plots because relief can introduce errors in distance and alignment.  Horizontal and vertical dimensional accuracy and azimuthal accuracy for the individual plots are:	
<b>(</b> 1	instruments, and image interpretation is performed with the aid of stereoscopic viewing equipment. Identifiable image points are measured and their coordinate values mathematically transformed by computer. This transformation corrects for camera and attitude (pitch, roll, and yaw) induced distortions, but does not correct for displacement due to ground relief and object height.  These target plots represent the most accurate data compiled to date, but the user is cautioned to exercise care in scaling distances or determining azimuths from these plots because relief can introduce errors in distance and alignment.  Horizontal and vertical dimensional accuracy and azimuthal accuracy for	
<b>(</b> 1	instruments, and image interpretation is performed with the aid of stereoscopic viewing equipment. Identifiable image points are measured and their coordinate values mathematically transformed by computer. This transformation corrects for camera and attitude (pitch, roll, and yaw) induced distortions, but does not correct for displacement due to ground relief and object height.  These target plots represent the most accurate data compiled to date, but the user is cautioned to exercise care in scaling distances or determining azimuths from these plots because relief can introduce errors in distance and alignment.  Horizontal and vertical dimensional accuracy and azimuthal accuracy for the individual plots are:	
<b>{</b> 1	instruments, and image interpretation is performed with the aid of stereoscopic viewing equipment. Identifiable image points are measured and their coordinate values mathematically transformed by computer. This transformation corrects for camera and attitude (pitch, roll, and yaw) induced distortions, but does not correct for displacement due to ground relief and object height.  These target plots represent the most accurate data compiled to date, but the user is cautioned to exercise care in scaling distances or determining azimuths from these plots because relief can introduce errors in distance and alignment.  Horizontal and vertical dimensional accuracy and azimuthal accuracy for the individual plots are:	
<b>{</b> {1	instruments, and image interpretation is performed with the aid of stereoscopic viewing equipment. Identifiable image points are measured and their coordinate values mathematically transformed by computer. This transformation corrects for camera and attitude (pitch, roll, and yaw) induced distortions, but does not correct for displacement due to ground relief and object height.  These target plots represent the most accurate data compiled to date, but the user is cautioned to exercise care in scaling distances or determining azimuths from these plots because relief can introduce errors in distance and alignment.  Horizontal and vertical dimensional accuracy and azimuthal accuracy for the individual plots are:	
<b>{</b> 1	instruments, and image interpretation is performed with the aid of stereoscopic viewing equipment. Identifiable image points are measured and their coordinate values mathematically transformed by computer. This transformation corrects for camera and attitude (pitch, roll, and yaw) induced distortions, but does not correct for displacement due to ground relief and object height.  These target plots represent the most accurate data compiled to date, but the user is cautioned to exercise care in scaling distances or determining azimuths from these plots because relief can introduce errors in distance and alignment.  Horizontal and vertical dimensional accuracy and azimuthal accuracy for the individual plots are:	




FIGURE 1. SARY-SHAGAN ANTIMISSILE TEST CENTER, USSR.

TOP SECRET

Approv	ed For Release 2004/	01/14 : CIA-RDP78T0	04759A006400010035-9	
	TOP SECRET			2 <b>5</b> 8)
	INT	RODUCTION		
Instrument	ation Site 15 <i>(47</i> -99N	I 067-29E) is the we	esternmost facility at the	
Sary-Shagan A	ntimissile Test Cent	er (SSATC). It is l	ocated 270 nautical miles	
	thwest of the headq ash (Figure 1).	uarters buildings a	t the Main Support Base	
Instrument	ation Site 15 is 1 of 5	areas where E-shap	ped buildings are located	
at the SSATC. 16, 17, and 18. S		are also located at .	Instrumentation Sites 14,	
10, 17, and 10.				
		SCRIPTION	Class sharement on whotog	
Instrumen raphy in	tation Site 15 (Figu	ires 2 and 3) was can be negated in	first observed on photog- When the	25X
site was first o	bserved it was in an	early stage of cons	struction. Grading for the	
E-shaped buildetails of site		at that time. See	chronology, Table 1, for	
The site	consists of the uniq	ue E-shaped buildi	ng, a second large opera-	
tions building support area.	g, an interferometer	site, a natural-surf	aced airstrip, and a small	
The E-sha	ped building at Inst	rumentation Site 1	5 consists of a rectangular	
main section	of the building (See		s attached to the in-range atton 42, Figure 5.) Three	
raised section	s are positioned on	the roof of the mai	n section in-line with the	
3 wings (anno	otations 42c). A recta	ngular-shaped struc s 42b). Each of the	ture is positioned on each	25X
		_		
A compari	ison of the 2 large-s	scale coverages of ed structures on th	e wings of the E-building	25X
are movable.	i.e., traverse the l	ong axis of the w	ing. Ineacn	25X
probably mov	able structure was	positioned near th	e end of the wing, but in sitioned flush against the	
raised portion	of the main section	n of the building.	See artist's concept, inset,	
Figure 5.)	aned building at Ins	strumentation Site	15 was under construction	
when the ent	ire site was first ob	served under const	ruction inCon-	25X
struction acti	vity was apparent a ar probably movabl	round the E-buildin e structures on th	g through However, e wings of the E-building	25X
were not cle	arly discernible un	itil A c	ompletion date for the E-	25X
	ot be pinpointed o pletion by mid-to-late		ı - but evidence points to	
A second	operations buildir	ng was first observ	yed under construction at	
Instrumentati externally cor			33, Figure 5.) It appeared and size equates with the	
main section (	of the E-building.			
A "stand struction at S		nterferometer was	first observed under con- es 6 and 7.) Four 500-foot	
legs formed	a plus-type configu	ration, with 3 anter	nna positions on each leg.	
	work began on 9,300 terferometer. By	orobable:	nsions for each leg of the antenna positions, forming	
L-shaped patt	terns, were under c	onstruction near th	e termini of the extended	
interferomete antenna posit		2 and 3.) Work was	still in progress on these	
		area remained stab	le, i.e., no new major ad-	
	observed, from		barracks building was con-	25X
structed in th	a large p e support area (anno			25X <sup>-</sup>
		- 1 -		∠5∧` 
Approv			04759A006400010035-9	
	TOP SECRE	:H		

FIGURE 2. INSTRUMENTATION SITE 15.

TOP SECRET

25X1

Approved For Release 200401/14 CIA TOP78T04759A006400010035-9


SCALE APPROX 1:2050

FIGURE 4. OPERATIONS AND SUPPORT AREA.

TOP SECRET

25X1

2**5**51



25X1<sup>--</sup>

25X1

25X1

Approved For Release 2004/01/14 : CIA-RDP78T04759A006400010035-9

FIGURE 5. LINE DRAWING OF OPERATIONS AND SUPPORT AREA, WITH INSET OF E-SHAPED BUILDING.

- 5 -

TOP SECRET

NPIC L-7330 (3/67)

25X1 25X1 TOP SECRET


28×1



FIGURE 6. INTERFEROMETER, SITE 15.

NPIC L-7331 (3/67)

25



25X1

Instrumentation Site 15 Chronology

## Remarks

Site activity negated.

Site first observed in early stage of construction. Two buildings are present. Grading for the E-shaped building is observed. See annotation 42, Figure 5. Extensive track activity throughout area.

Five buildings now present in support area.

Eleven buildings present in support area. The walls of the E-building are under construction. A motor pool and open storage areas are identified.

Thirteen buildings present in support area. Roof is complete on main section of E-building but construction activity continues at wings. A natural-surfaced airstrip has been graded just north of support area. Initial grading for interferometer site is observed.

Fourteen buildings present in support area. No apparent change at E-buildings (imagery poor). Four legs are visible at interferometers. Each extends approximately 500 feet from center.

Sixteen buildings present in support area. Construction activity apparent at wings of E-building. Northeast corner of E-building (80 by 25 feet) is dark in tone. Interferometer grading appears complete (1,000-foot diameter circle).

No significant change since

Eighteen buildings observed in support area. No significant change in remainder of site.

No change in support area, airfield, or interferometer. The 2 concrete aprons located on either side of Ebuilding are observed for first time and are unoccupied. The foundation for the second operations building is observed. See annotation 33, Figure 5.

No change in support area of airfield. Much activity is visible in the operations area, i.e., unidentified vehicles/equipment and open storage of materials. Each concrete pad at E-building has 2 unidentified vehicles/ equipment positioned on it. Roof appears complete on second operations building (annotation 33, Figure 5). Central control bunker is under construction at interferometer. Cable scar is observed connecting second operations building with E-building.

The 2 environmental domes and possible antenna (annotations 43-45, Figure 5) located in front of the wings of the E-building are observed for first time.

No apparent change since

Scarring for interferometer leg extensions observed for first time.

No apparent change since

Large probable 2-story barracks building under construction (annotation 18, Figure 5).

Large barracks building appears externally complete. Scarring for all 4 interferometer leg extensions clearly visible. Scarring is also observed at positions which form L-shaped patterns at east, west, and north legs. The large microwave tower is observed for first time (annotation 46, Figure 5).

The U/I structures on wings of E-building (1 on each wing) are observed positioned near the ends of the wings (annotation 42, Figure 5). The horizontal dipole antenna is identified (annotations 37-38, Figure 5). Antennas on interferometers are identified (annotations 2-4, Figure 7). Small probable electronic equipment buildings

extension (Figure 3). U operations building are Fig 5).  No apparent change since This mission was used line drawings in this good-quality, large-scale,	inus of each interferometer leg /I excavations south of second first observed (annotation 36,  as the basic source for the 3 report. The mission provided stereo coverage of the te - the best coverage of the	25X1 25X
site to date. REFERENCES		25X1
	index 21)	25X1

**X**1

**5** (1

25X1	Approved For Potence #904404/44 : CIA_PDP78T04759A0064000100R5_9
	Approved For Fightpuse 2004(01/14: CIA-RDP78T04759A0064000100β5-9

AMS. Series DESPA-1, Sheet NL 42-1, 1st ed, Nov 64, scale 1:250,000 (TOP SECRET

REFERENCES (Continued)

DOCUMENT
1. CIA. E-Shaped Buildings, Sary-Shagan Antimissile Test Center, USSR, Mar 65 (TOP SECRET
RELATED DOCUMENTS
NPIC. Instrumentation Site 15, SSATC, USSR, Sep 66 (TOP SECRET NPIC. MSG-8393, 7 Sep 66 (TOP SECRET
MAPS OR CHARTS

REQUIREMENT

CIA. C-D15-82,750 (revised)

NPIC PROJECT

11023/66 (partial answer)